

**STANDARD MOUNTABLE "V" TYPE  
COMBINATION CURB & GUTTER**




12", 18", 24", 36", GUTTER PAN ; 8" DEPTH

12", 18", 24", 36", GUTTER PAN ; 9" DEPTH

12", 18", 24", 36", GUTTER PAN ; 10" DEPTH

**NOTES:**

1. JOINT SPACING FOR MOUNTABLE "V" TYPE CURB IS 10 FEET
2. SEE SPECIFICATIONS FOR LOCATIONS AND DESCRIPTION OF TREATMENT FOR THE TYPES OF JOINTS USED.
3. UNLESS OTHERWISE SPECIFIED: A LONGITUDINAL TIE DEVICE PLACED AT MIDDLE OF KEYWAY (NOT SHOWN), SHALL BE USED AT CONSTRUCTION JOINT BETWEEN MOUNTABLE "V" TYPE CURB AND RIGID PAVEMENT. SEE BC 572.61-1.

	APPROVED:  DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION  DIRECTOR, DEPARTMENT OF TRANSPORTATION	<b>CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION TRANSPORTATION ENGINEERING AND CONSTRUCTION</b>	ISSUED 8 / 2010	REVISED 	REVISED 	
	<b>STD. MOUNTABLE "V" TYPE COMBINATION CURB &amp; GUTTER</b>			<b>STANDARD NO. BC 620.04</b>		
				SCALE : NONE	SHEET 1 OF 1	