




MONOLITHIC CONCRETE MEDIAN

TYPE 'A'

USE WITH FLEXIBLE PAVEMENT

NOTES

- ON BOTH SIDES OF MEDIAN, USE CURB FACE TYPE 'A' OR TYPE 'A' MOD. AS CALLED FOR OR SHOWN ON PLANS. SEE BC 620.01, BC 645.04 AND BC 645.05.
- JOINTS WILL BE SPACED 10'-0" APART (SIMILAR TO JOINTS FOR CONCRETE CURBS AND COMBINATION CURB & GUTTER). PROVIDE A DUMMY GROOVE ($\frac{1}{2}$ " DEEP) AT 5 - FOOT INTERVALS BETWEEN JOINTS.
- SPECIFICATIONS FOR CONCRETE CURB AND COMBINATION CONCRETE CURB & GUTTER WILL APPLY.

	APPROVED:  DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION  DIRECTOR, DEPARTMENT OF TRANSPORTATION	CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION TRANSPORTATION ENGINEERING AND CONSTRUCTION	ISSUED 8 / 2010	REVISED	REVISED
	MONOLITHIC CONCRETE MEDIAN TYPE 'A'		STANDARD NO. BC 645.01		
			SCALE: NONE	SHEET 1 OF 1	