




**MONOLITHIC CONCRETE MEDIAN
TYPE 'B'**

USE WITH FLEXIBLE PAVEMENT

NOTES:

1. ON BOTH SIDES OF MEDIAN, USE CURB FACE TYPE 'A' OR TYPE 'A' MOD. AS CALLED FOR OR SHOWN ON PLANS. SEE BC 620.01, BC 645.04 AND BC 645.05.
2. JOINTS WILL BE SPACED 10'-0" APART (SIMILAR TO JOINTS FOR CONCRETE CURBS AND COMBINATION CURB & GUTTER). PROVIDE A DUMMY GROOVE (1/2" DEEP) AT 5 - FOOT INTERVALS BETWEEN JOINTS.
3. SPECIFICATIONS FOR CONCRETE CURB AND COMBINATION CONCRETE CURB & GUTTER WILL APPLY.

	APPROVED:  DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION	CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION TRANSPORTATION ENGINEERING AND CONSTRUCTION	ISSUED	REVISED	REVISED
	 DIRECTOR, DEPARTMENT OF TRANSPORTATION		MONOLITHIC CONCRETE MEDIAN TYPE 'B'	8 / 2010	
				STANDARD NO. BC 645.02	
			SCALE: NONE	SHEET 1 OF 1	