




## MONOLITHIC CONCRETE MEDIAN TYPE 'C'

USE WITH RIGID PAVEMENT

### NOTES

1. ON BOTH SIDES OF MEDIAN, USE CURB FACE TYPE 'A' OR TYPE 'A' MOD. AS CALLED FOR ON PLANS. (SEE BC 620.01, BC 645.04 AND BC 645.05)
2. JOINTS WILL BE SPACED 10'-0" APART (SIMILAR TO JOINTS FOR CONCRETE CURBS AND COMBINATION CURB & GUTTER). PROVIDE A DUMMY GROOVE (1/2" DEEP) AT 5-FOOT INTERVALS BETWEEN JOINTS.
3. SPECIFICATIONS FOR CONCRETE CURB AND COMBINATION CONCRETE CURB & GUTTER WILL APPLY.

|   |   |   |  |   |              |              |
|---|---|---|--|---|--------------|--------------|
|  | APPROVED:   | <b>CITY OF BALTIMORE</b><br><b>DEPARTMENT OF TRANSPORTATION</b><br><b>TRANSPORTATION ENGINEERING AND CONSTRUCTION</b> | ISSUED   | REVISED                                 | REVISED      |              |
|   | <br>DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION<br><br>DIRECTOR, DEPARTMENT OF TRANSPORTATION |   | <b>MONOLITHIC CONCRETE MEDIAN</b><br><b>TYPE 'C'</b> | 8 / 2010                                |              |              |
|   |   |   |  | <b>STANDARD NO.</b><br><b>BC 645.03</b> | SCALE : NONE | SHEET 1 OF 1 |